

C5e PATCH PANEL UTP 50u

單位:mm

產品編號 : 17340

產品品名 : 3A-EPLM-481BKZ

台製 3ANET 模組式 2U 19吋 48 Ports

C5e Patch Panel 網路跳線面板 黑色

Performance:

Meets C5e EIA/TIA 568B Standard.

Materials:

Front Plate	: Fireproof ABS UL-94V0
Panel	: Metal (SPCC)
Jack	: 8P8C 50 micro inches gold plated
PCB	: FR-4 / UL-94V0
IDC Cap	: Fireproof ABS UL-94V0
IDC Body	: Fireproof ABS UL-94V0
IDC Pin	: Bronze & Tinned

IDC Description : For 22-26 AWG.

For 110 punch-down Tool

Electrical Specifications:


Insulation Resistance : 500M ohms (min.)

Contact Resistance : 20m ohms (max.)

Current Rating : 1.5 Amps .

DC Resistance : 0.1 ohms (max.)

Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.



Mechanical Specifications:

IDC Punch Down Cycle : Over 250 Cycles (min.)

Jack Insertion Cycle : Over 2000 Cycles (min.)

Operation Temperature : -40 °C ~ +70 °C