

# C6 PATCH PANEL UTP 50u

單位:mm

產品編號 : 18270

產品品名 : 3A-6PA89M-081BKZ

台製 3ANET 模組式 89 Type 8 Ports

C6 Patch Panel 網路跳線面板 (鋁板) 黑色

## Performance:

Meets C6 EIA/TIA 568B Standard.

## Materials:

Panel	: Metal (Aluminum)
Body	: Fireproof ABS UL-94V0
Jack	: 8P8C 50 micro inches gold plated
PCB	: FR-4 / UL-94V0
IDC Cap	: Fireproof ABS UL-94V0
IDC Body	: Fireproof ABS UL-94V0
IDC Pin	: Bronze & Tinned

IDC Description : For 22-26 AWG.

For 110 punch-down Tool

## Electrical Specifications:

Insulation Resistance : 500M ohms (min.)

Contact Resistance : 20m ohms (max.)

Current Rating : 1.5 Amps .

DC Resistance : 0.1 ohms (max.)

Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

## Mechanical Specifications:

IDC Punch Down Cycle : Over 250 Cycles (min.)

Jack Insertion Cycle : Over 2000 Cycles (min.)

Operation Temperature : -40 °C ~ +70 °C

