

C6 PATCH PANEL UTP 50u

單位:mm

產品編號 : 18290

產品品名 : 3A-6PM89M-081BKZ

台製 3ANET 模組式 89 Type 8 Ports

C6 Patch Panel 網路跳線面板 (鐵板) 黑色

Performance:

Meets C6 EIA/TIA 568B Standard.

Materials:

Front Plate	: Metal (SPCC)
Body	: Fireproof ABS UL-94V0
Jack	: 8P8C 50 micro inches gold plated
PCB	: FR-4 / UL-94V0
IDC Cap	: Fireproof ABS UL-94V0
IDC Body	: Fireproof ABS UL-94V0
IDC Pin	: Bronze & Tinned

IDC Description : For 22-26 AWG.

For 110 punch-down Tool

Electrical Specifications:

Insulation Resistance	: 500M ohms (min.)
Contact Resistance	: 20m ohms (max.)
Current Rating	: 1.5 Amps .
DC Resistance	: 0.1 ohms (max.)
Withstanding Voltage	: 1000 VAC RMS @ 60Hz / 1 min.

Mechanical Specifications:

IDC Punch Down Cycle	: Over 250 Cycles (min.)
Jack Insertion Cycle	: Over 2000 Cycles (min.)

Operation Temperature : -40 °C ~ +70 °C

