

C3 KEYSTONE JACK UTP 6u

單位:mm

產品編號 : 24004

產品品名 : 3A-3KTVM-U1WH666Z

台製 3ANET 窄型 RJ12 C3 Keystone Jack 白色

可安裝於面板 / 桌盒 / 19"鐵板

Performance:

Meets C3 Standard.

Materials:

Body : Fireproof ABS UL-94V0
Jack : 6P6C 6 micro inches gold plated
PCB : FR-4 / UL-94V0
IDC Cap : Fireproof ABS UL-94V0
IDC Body : Fireproof ABS UL-94V0
IDC Pin : Bronze & Tinned

IDC Description : For 22-26 AWG.

For 110 punch-down Tool

Electrical Specifications:

Insulation Resistance : 500M ohms (min.)
Contact Resistance : 20m ohms (max.)
Current Rating : 1.5 Amps .
DC Resistance : 0.1 ohms (max.)
Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

Mechanical Specifications:

IDC Punch Down Cycle : Over 250 Cycles (min.)
Jack Insertion Cycle : Over 2000 Cycles (min.)

Operation Temperature : -40 °C ~ +70 °C

用網路線 (USOC)	1	2	3	4	5	6	X	X
用6C電話線(AT&T)	1	2	3	4	5	6		
用4C電話線(AT&T)		2	3	4	5			
用2C電話線(AT&T)			3	4				

本產品線位貼紙是依照USOC的線位標示

若是用電話線請參照USOC相對線位打線

