

# C5e KEYSTONE JACK UTP 50u (免工具式)

單位:mm

產品編號 : 24044

產品品名 : 3A-EKTVNL-U1WHZ

台製 3ANET 免使用打線工具的 RJ45 C5e Tooless Keystone Jack 白色

可安裝於面板 / 桌盒 / 19"鐵板

## Performance:

Meets C5e EIA/TIA 568B Standard.

## Materials:

Body : Fireproof ABS UL-94V0  
Jack : 8P8C 50 micro inches gold plated  
PCB : FR-4 / UL-94V0  
IDC Cap : Fireproof PC  
IDC Body : Fireproof ABS UL-94V0  
IDC Pin : Phosphor Bronze & Tinned

IDC Description : For 22-26 AWG.

For 110 or Krone punch-down Tool  
Tooless (when use IDC cap directly)

## Electrical Specifications:

Insulation Resistance : 500M ohms (min.)  
Contact Resistance : 20m ohms (max.)  
Current Rating : 1.5 Amps .  
DC Resistance : 0.1 ohms (max.)  
Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

## Mechanical Specifications:

IDC Punch Down Cycle : Over 250 Cycles (min.)  
Jack Insertion Cycle : Over 2000 Cycles (min.)

Operation Temperature : -40 °C ~ +70 °C

