

C6A KEYSTONE JACK UTP 50u (免工具式)

單位:mm

產品編號 : 24150

產品品名 : GKTHL-U1BKSZ-72

台製 窄型180° 免使用打線工具的 RJ45 C6a UTP Tooless
Keystone Jack 黑色

可安裝於面板 / 桌盒 / 19"鐵板

SPECIFICATION

Meets ANSI/TIA-568-C.2 Category 6A Connecting Hardware

Electrical

Insulation Resistance : 500 MΩ minimum @ 100 Vdc
Dielectric Withstanding Voltage : 1000 Vac rms @ 60Hz
for one minute

Current Rating : 1.5 Amps
Spring wire contact resistance : 20 mΩ maximum
IDC contact resistance : 2.5 mΩ maximum

Mechanical

Total Contact force : >100 GRAMS per contact wire lead
Retention : 50 N(11 lbf) for 60s ± 5s
Durability : 750 cycles minimum
Conductor compatibility : 22 ~ 24 AWG
Temperature range storage : -40° C ~ +70° C
Temperature range operation : -10° C ~ +60° C
Relative humidity operation : Maximum noncondensing 93%

Materials

Housing : High Impact flame retardant plastic, UL 94 V-0 Rated
PCB : FR4, 1.6mm thickness
Spring wire : Phosphor Bronze Alloy plated with 50 micro-inch
of gold over 70~100 micro-inch of nickel
IDC : Phosphor Bronze alloy plated with 100 micro-inch of tin

