

C6 PATCH PANEL UTP 50u

單位 mm

產品編號 : 18009

產品品名 : 3A-6PM229M-081GYZ

台製 3ANET C6 8 Ports 模組式網路跳線面板 宅內箱適用 灰色

Performance:

Meets C6 EIA/TIA 568B Standard.

Materials:

Front Plate	: Fireproof ABS UL-94V0
Panel	: Metal (SPCC)
Jack	: 8P8C 50 micro inches gold plated
PCB	: FR-4 / UL-94V0
IDC Cap	: Fireproof ABS UL-94V0
IDC Body	: Fireproof ABS UL-94V0
IDC Pin	: Bronze & Tinned

IDC Description : For 22-26 AWG.

For 110 punch-down Tool

Electrical Specifications:

Insulation Resistance : 500M ohms (min.)
Contact Resistance : 20m ohms (max.)
Current Rating : 1.5 Amps .
DC Resistance : 0.1 ohms (max.)
Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

Mechanical Specifications:

IDC Punch Down Cycle : Over 250 Cycles (min.)
Jack Insertion Cycle : Over 2000 Cycles (min.)

Operation Temperature : -40 °C ~ +70 °C

